

# HERCULES

Spur Geared  
Chain Pulley Block

**Features :**  
Automatic Double Pawl  
Braking System  
Load Wheel : Alloy Steel-Heat  
Treated-Mounted On Ball  
BEARINGS

**WARRANTY :**  
We Provide one Year's  
Warranty against any  
manufacturing defects  
Ex. Our works



Mfgr. By:

**ISHAR HOIST & CRANES PVT. LIMITED**

A-458, M.I.D.C., T.T.C. Indl. Area, Mahape, Navi Mumbai - 400710.

Tele. : +91 22 27780111 / 0101 / 0123. Fax : +91 22 27781347

E-mail : isharhoist@gmail.com / sales@isharhoist.com

Web : www.isharhoist.com



AN ISO 9001-2008 CO.

# HERCULES

## Spur Geared Chain Pulley Block

### Charateristics

- ❖ Capacity range from 1 Ton. to 25 Ton.
- ❖ Automatic double pawl braking system.
- ❖ Sealed bearings.
- ❖ Light weight robust construction.
- ❖ Low effort to lift maximum load.
- ❖ Double cover protection.
- ❖ Extra thick friction discs.
- ❖ Alloy Steel Grade 80-Load Chain.
- ❖ Zinc plated hand chain as standard.
- ❖ Built in overload protection device.
- ❖ Each Chain Block is proof tested to 50% overload.
- ❖ Fully forged hooks are fitted with safety latches as standard.

### Chain Pulley Block Specifications :

SIML	1	2	3	5	7.5	10	15	20	25
Standard Lift	2	3	3	3	3	3	3	3	3
Effort Required to Lift Rated Load-Kgs.	25	35	40	37	37	40	38	40	40
No. of Falls of Load Chain	1	1	1	2	3	4	6	8	10
Load Chain Diameter	mm	6	8	10	10	10	10	10	10
	A	151	175	205	189	189	189	189	200
	B	172	210	255	280	433	463	776	900
	C	376	470	548	688	690	765	900	950
	D	40	50	55	65	67	85	95	106
	K	27	35	39	45	47	54	70	80
Net Weight with 3M. Lift-Kgs.		13	20	35	41.3	62	79	135	190

